

## Cisco Aironet 340 Series Workgroup Bridges **In-Building or Building-to-Building** Wireless Solutions

THE CISCO AIRONET WORKGROUP BRIDGE SERIES PROVIDES FLEXIBLE WIRELESS NETWORK CONNECTIONS FOR UP TO EIGHT ETHERNET DEVICES.

Cisco Aironet 340 Series Workgroup Bridge



Designed to meet the needs of mobile users, remote workgroups or satellite offices, the Cisco Aironet® 340 series workgroup bridge links up to eight Ethernet clients to a wireless LAN. Equipped with a standard Ethernet connector, the workgroup bridge connects to a single Ethernet device or, for up to eight devices, to a 10BaseT (RJ45) port of an Ethernet hub. The workgroup bridge communicates with Cisco Aironet 340 series access points or wireless bridges.

The workgroup bridge quickly connects an Ethernet-enabled laptop or other portable computer to a network and provides a plug-and-play solution for e-mail and Internet access. No drivers need to be installed, making it an ideal solution for the business traveler. Any Ethernet-ready device, including printers, copiers, PCs, point-of-sale devices, or monitoring equipment, can be placed directly at the point of work using the workgroup bridge—without the expense or delay of cabling. For temporary classrooms or temporary office space, the workgroup bridge provides flexible, easy network access for up to eight devices. Equipment can be easily moved as workgroups change in number or location, lowering facilities costs.

In a campus environment, the workgroup bridge connects workgroups in separate buildings, quickly and economically. The workgroup bridge can be located up to 10 miles away (about half of the distance of a wireless bridge) with clear line-of-sight from a Cisco Aironet 340 series wireless bridge by using an optional long-range antenna. The workgroup bridge eliminates cable installation costs and allows for quick redeployment of equipment when expanding or moving to a new location.

The workgroup bridge is available with a single omnidirectional dipole antenna. An option with two RP-TNC (reverse polarity threaded naval connector) connectors is also available for applications that require antenna diversity or higher-gain antennas for long-range applications. Using direct sequence spread spectrum (DSSS) technology, the workgroup bridge operates in the unlicensed 2.4 GHz band and supports data rates up to 11 Mbps. Understanding the security requirements of small- and medium-sized businesses as well as the enterprise, Cisco provides 40-bit and 128-bit Wired Equivalent Privacy (WEP) to provide data security equal to traditional wired networks. Other features include advanced diagnostic tools to simplify troubleshooting, remote system configuration and management via browser, Telnet, FTP or SNMP. The workgroup bridge:

- Links single devices or workgroups of up to eight clients to a LAN
- Attaches to any standard Ethernet hub for applications connecting 2-8 Ethernet-ready devices
- Simple client installation, with no drivers required
- Offers up to 11 Mbps data rate
- Supports long ranges outdoors with optional antennas

Figure 1 Mobile Ethernet enabled user connecting to a workgroup bridge




Figure 2 A remote workgroup





Figure 3 Satellite office



### Cisco Aironet 340 Series Workgroup Bridge Specifications

Physical	
Status Indicators	Three indicators on the top panel: radio traffic, Ethernet traffic and status
Connectors	On the back panel: barrel power connector (plug-in for AC adapter) and RJ-45 Ethernet connector
Power Supply	Standard power pack (120VAC/60Hz) Universal power pack (90-264VAC/47-63Hz)
Temperature	32° F to 122° F (0° C to 50° C)
Humidity	10 to 90 percent noncondensing
Dimensions	6.3 in x 4.72 in x 1.45 in (16 cm x 12 cm x 3.7 cm)
Weight	Less than 1 lb. (0.45 kg.) excluding power supply
Radio	
Frequency	2.400 to 2.497 GHz
Range When Communicating to a 340 Series Access Point (typical)	Indoor office: 100 ft. (30 m) at 11 Mbps; 300 ft. (91 m) at 1 Mbps Outdoor (with standard dipole): 400 ft. (122 m) at 11 Mbps; 1,500 ft. (460 m) at 1 Mbps
Receive Sensitivity	-90 dBm@ 1 Mbps -88@ 2 Mbps -87@ 5.5 Mbps -84 @ 11 Mbps
Modulation	DBPSK @ 1 Mbps DQPSK @ 2 Mbps CCK @ 5.5 and 11 Mbps

## Cisco Aironet 340 Series Workgroup Bridge Specifications

<b>Output Power</b>	30 mW (15 dBm)
<b>Wireless Medium</b>	Direct Sequence Spread Spectrum
<b>Operating Channels</b>	11 Channels (US, Canada and Japan) 13 Channels (ETSI)
<b>Simultaneous Channels</b>	Three
<b>Data Rates</b>	1, 2, 5.5 and 11 Mbps
<b>Network Information</b>	
<b>Network Architecture Type</b>	Infrastructure via a Cisco Aironet access point or bridge
<b>Device Drivers</b>	None required
<b>Network Support</b>	Transparent TCP/IP
<b>Network Connection Type</b>	10BaseT
<b>Network Protocols Supported</b>	IEEE 802.3 and Ethernet blue book
<b>Security</b>	System ID required, up to 32 ASCII characters 40-bit WEP and 128-bit WEP available
<b>General</b>	
<b>Antenna</b>	Single captured 2.2 dBi antenna or two (diversity) RP-TNC connectors for use with optional antennas
<b>Certification</b>	Operates license-free under FCC Part 15 and complies as a Class B device. Complies with DOC regulations. Complies with ETS 300.328, FTZ 2100 and MPT 1349 standards. Call for other information on use outside of the USA.
<b>Warranty</b>	One year

## Cisco Aironet 340 Series Ordering Information

Product Number	Description
<b>AIR-WGB341C</b>	340 Series 11 Mbps DSSS Workgroup Bridge w/ 40-bit WEP & Captured Antenna
<b>AIR-WGB342C</b>	340 Series 11 Mbps DSSS Workgroup Bridge w/ 128-bit WEP & Captured Antenna
<b>AIR-WGB341R</b>	340 Series 11 Mbps DSSS Workgroup Bridge w/ 40-bit WEP & RP-TNC
<b>AIR-WGB342R</b>	340 Series 11 Mbps DSSS Workgroup Bridge w/ 128-bit WEP & RP-TNC



### Corporate Headquarters

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
www.cisco.com  
Tel: 408 526-4000  
800 553-NETS (6387)  
Fax: 408 526-4100

### European Headquarters

Cisco Systems Europe  
11, Rue Camille Desmoulins  
92782 Issy Les Moulineaux  
Cedex 9  
France  
www.cisco.com  
Tel: 33 1 58 04 60 00  
Fax: 33 1 58 04 61 00

### Americas Headquarters

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
www.cisco.com  
Tel: 408 526-7660  
Fax: 408 527-0883

### Asia Pacific Headquarters

Cisco Systems Australia, Pty., Ltd  
Level 17, 99 Walker Street  
North Sydney  
NSW 2059 Australia  
www.cisco.com  
Tel: +61 2 8448 7100  
Fax: +61 2 9957 4350

Cisco Systems has more than 190 offices in the following countries. Addresses, phone numbers, and fax numbers are listed on the [Cisco.com Web site at www.cisco.com/go/offices](http://www.cisco.com/go/offices).

Argentina • Australia • Austria • Belgium • Brazil • Canada • Chile • China • Colombia • Costa Rica • Croatia • Czech Republic • Denmark • Dubai, UAE Finland • France • Germany • Greece • Hong Kong • Hungary • India • Indonesia • Ireland • Israel • Italy • Japan • Korea • Luxembourg • Malaysia Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal • Puerto Rico • Romania • Russia • Saudi Arabia • Singapore Slovakia • Slovenia • South Africa • Spain • Sweden • Switzerland • Taiwan • Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela